

Expired product name: ROKU® 850 Fire Protection Putty

KERAFIX® Firestop Putty

Material of building material classification B2 (normal flammability) according to DIN 4102-1
Classification E (normal flammability) according to DIN EN 13501-1

General building approval Z-19.11-1746
European technical approval ETA-13/0666

Product Description

KERAFIX® Firestop Putty is single component intumescent fire protection mass on the basis of acrylate. KERAFIX® Firestop Putty does not contain halogenated compounds that would generate corrosive or toxic gases in case of fire.

Application Areas

- Joints between non-bearing separating walls
- Connections between wall and ceiling or floor
- Openings, cracks, grooves, hollow spaces and joints
- Fire protection doors and glazing
- Pipe ducts, cable ducts

Technical Data

Composition:	Solvent and halogen free one-component sealing material
Material structure:	Past-like, elastic material
Raw density [kg/m ³]:	1390 (± 10 %)
Reaktionsbeginn [°C]:	From ca. 140
Start of reaction [°C]:	14,5 to 20-times (450 °C; 30 min; without load)
Direction of action:	Three-dimensional
Forming inflatable body:	Solid, thermally insulating mass
Foaming pressure [N/mm ²]:	At least 0,8
Colour:	Black

Supplied Forms

Standard containers: 310 ml cartridge

Please read the safety data sheet!

Processing and Storage

Processing: Use suitable devices (e.g. hand or compressed air gun) to apply
Storage: Store in a dry place between + 5 °C and + 30 °C; original, closed cartridges can be stored ca. 12 months after date of filling.

*Ensure that surfaces are free from dust, fat or oil! Close opened cartridges air-tight and use as fast as possible!
Protect from frost or heat! Store product horizontally!*

Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trade mark rights and existing laws and regulations. Adhesive bonds are to be applied according to DIN 2304.

