


KERAFIX® Flexting 100

Material of building material classification B2 (normal flammability) according to DIN 4102-1

Product Description

KERAFIX® Flexting 100 is a flexible, intumescent material on the basis of exfoliated graphite that foams up under pressure with thermal influence.



Application Areas

- Fire protection doors from steel or aluminium
- Safety cabinets, control cabinets
- In drywall construction: Ceiling constructions

Technical Data

Composition:	Foaming construction material on the basis of foaming graphite
Material structure:	Firm, flexible roll material
Raw density [kg/m ³]:	1300 (±10 %)
Start of reaction [°C]:	From ca. 190
Foaming rate [x-times]:	8 to 15 times (450 °C; 30 min; without load)
Direction of action:	Three-dimensional
Foaming pressure [N/mm ²]:	At least 0,6

Executed Variants

KERAFIX® Flexting 100 without additional lamination

Variant SK: One-sided adhesive

Further variants on request.

All variants – cut formats or formed parts (according to DIN 7715-5) may be equipped with various adhesive tapes.

Supplied Forms

Standard lengths: 25000 mm and 50000 mm

Widths: Up to 320 mm

Thicknesses: 1,5 mm and 2 mm (Special thicknesses available on request)

Special formats are available on request. The product is manufactured on the basis of the general tolerance DIN ISO 2768-1.

Please read the safety data sheet!

Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trade mark rights and existing laws and regulations.

Corresponds to DIN 2304.