


## ROKU® Fire Resistant Grille F

### Product Description

The ROKU® Fire Resistant Grille F permits free air exchange in apertures of construction components. The fire resistant grille consists of a plaster board and coated fins that foam up in case of fire.



### Application Areas

- Overflow apertures
- Air vent openings in walls
- Fire protection housings (e.g. control cabinets)
- In walls with fire resistance grading F 30 - F 90
- Massive walls, light separating walls and massive ceilings

### Construction Options Suitable for

F 30:	1 fire resistant grille (20 mm)
F 60:	2 fire resistant grilles combined (40 mm)
F 90:	3 fire resistant grilles combined (60 mm)

### Supplied Forms

Widths:	100 mm or 200 mm
Height:	100 mm
Depths:	20 mm, 40 mm or 60 mm

### Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trade mark rights and existing laws and regulations. Adhesive bonds are to be applied according to DIN 2304.