

Flammi 22

Material of building material classification A1 (non flammable) according to DIN 4102-1

Product Description

Flammi 22 is a cement-bound, dimensionally stable silicate glazing block.



Application Areas

- Fire protection doors from wood, steel or aluminium
- Fire protection glazing
- Applications in construction of chimneys, stoves and ovens

Technical Data

Composition:	Cement-bound construction material on the basis of silicate
Material structure:	Hard material
Raw density [kg/m ³]:	Ca. 870 (± 15 %)

Supplied Forms

Length:	80 mm
Widths:	8 mm to 40 mm
Thicknesses:	6 mm, 8 mm, 10 mm, 12 mm, 15 mm

Special formats are available on request. The product is manufactured on the basis of the general tolerance DIN ISO 2768-1.

Please read the safety data sheet!

Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trade mark rights and existing laws and regulations. Adhesive bonds are to be applied according to DIN 2304.